

PATENT
Atty. Dkt. No. DIVA/245CIP3**AMENDMENTS FOR THE CLAIMS**

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

- Sub E17*
- D/cont*
1. (Currently amended) An apparatus for encoding realtime and non-realtime contents, the apparatus comprising:
 - ~~a non-realtime content source configured to provide non-realtime content;~~
 - ~~a first non-realtime encoder coupled to the non-realtime content source and configured to encode the non-realtime content into encoded non-realtime content slices;~~
 - ~~a realtime content source configured to provide realtime content;~~
 - ~~a second realtime encoder coupled to the realtime content source and configured to encode the realtime content into encoded realtime content slices for storing said realtime content in a grid page database wherein said realtime content comprises intra-coded slices and predictively coded slices stored separately within said grid page database;~~
 - ~~a remultiplexer operatively coupled to the non-realtime encoder and the realtime encoder and configured to repacketize the encoded non-realtime content slices and the encoded realtime content slices into transport packets suitable for transmission in a transport stream; and~~
 - ~~a re-timestamp unit coupled to the remultiplexer and configured to provide timestamps to be applied to the transport packets in order to synchronize the realtime and non-realtime content contents.~~
 2. (Previously presented) The apparatus of claim 1, where the apparatus is located within a head-end of a cable distribution system.
 3. (Previously presented) The apparatus of claim 1, further comprising:
 - a clock unit configured to provide a clock signal to the re-timestamp unit and to generate a clock stream to be transmitted along with the transport stream to a plurality of terminals.

PATENT

Atty. Dkt. No. DIVA/245CIP3

4. (Previously presented) The apparatus of claim 1, further comprising:
a rate control unit configured to determine an encoding rate for the non-realtime content and to provide the determined encoding rate for the non-realtime content to the non-realtime encoder.
5. (Previously presented) The apparatus of claim 4, where encoding rate for the non-realtime content is determined based at least in part on an output rate of the transport stream.
6. (Previously presented) The apparatus of claim 4, where the rate control unit determines an encoding rate for the realtime content based at least in part on an output rate of the transport stream.
7. (Previously presented) The apparatus of claim 1, wherein the realtime content includes video and audio contents.
8. (Previously presented) The apparatus of claim 1, wherein the non-realtime content includes guide data.
9. (Previously presented) The apparatus of claim 7, wherein the realtime encoder includes
a video encoder configured to encode the realtime video content, and
an audio encoder configured to encode the realtime audio content.
10. (Previously presented) The apparatus of claim 5, wherein the encoding rate for the non-realtime content is further determined based on a maximum bit rate anticipated for the encoded realtime content.
11. (Previously presented) The apparatus of claim 1, wherein the timestamps provided by the re-timestamp unit replace timestamps generated by the realtime and non-realtime encoders.

PATENT

Atty. Dkt. No. DIVA/245CIP3

12. (Previously presented) The apparatus of claim 1, further comprising:
a slice combiner coupled to the realtime and non-realtime encoders and the remultiplexer, the slice combiner configured to combine slices of encoded realtime content with slices of encoded non-realtime content.
13. (Currently amended) The apparatus of claim 1, wherein realtime and non-realtime contents intended to be displayed in a single frame are re-timestamped by the re-timestamp unit for synchronization such that the contents are decoded and presented in the same frame.
14. (Currently amended) A method for encoding realtime and non-realtime contents, comprising:
encoding realtime content to generate encoded realtime content slices ~~for storing said realtime content in a grid page database wherein said realtime content comprises intra-coded slices and predictively coded slices stored separately within said grid page database;~~
encoding non-realtime content to generate encoded non-realtime content slices;
repacketizing the encoded realtime content slices and the encoded non-realtime content slices into transport packets ~~suitable for transmission in a transport stream;~~ and
re-timestamping the transport packets with new timestamps in order to synchronize the realtime and non-realtime content ~~contents~~.
15. (Previously presented) The method of claim 14, further comprising:
generating the new timestamps based on a common clock signal.
16. (Previously presented) The method of claim 14, further comprising:
controlling a bit rate for the encoded non-realtime content based in part on a bit rate for the transport stream.

PATENT

Atty. Dkt. No. DIVA/245CIP3

17. (Previously presented) The method of claim 16, wherein the bit rate for the encoded non-realtime content is further based on a maximum bit rate anticipated for the encoded realtime content.
18. (Previously presented) The method of claim 16, further comprising:
allocating the bit rate for the encoded non-realtime content among a plurality of pages of non-realtime content.
19. (Previously presented) The method of claim 14, further comprising:
combining slices of encoded realtime content with slices of encoded non-realtime content, and
wherein the repacketizing is based on the combined slices of encoded realtime and non-realtime contents.
20. (Withdrawn) A terminal configured to provide a user interface having includes therein realtime and non-realtime contents, comprising:
a demodulator operative to receive and demodulate a modulated signal to provide a transport stream;
a transport de-multiplexer coupled to the demodulator and operative to receive and process the transport stream to provide a sequence of transport packets re-timestamped to synchronize encoded realtime content and encoded non-realtime content included therein; and
at least one video decoder coupled to the transport de-multiplexer and operative to receive and decode the encoded realtime and non-realtime contents to recover the realtime and non-realtime contents for the user interface.
21. (New) The apparatus of claim 1 wherein said non-realtime content comprises guide page information and said realtime content comprises video and audio information.

PATENT

Atty. Dkt. No. DIVA/245CIP3

CONCLUSION

If, the Examiner believes that there are any unresolved issues requiring adverse final action in any of the claims now pending in the application, it is requested that the Examiner telephone Eamon J. Wall, Esq. or Frank Tolin, Esq. at (732) 530-9404 so that appropriate arrangements can be made for resolving such issues as expeditiously as possible.

Respectfully submitted,

Dated: 8/26/03E. J. Wall

Eamon J. Wall
Registration No. 39,414
Attorney for Applicants

MOSER, PATTERSON & SHERIDAN, LLP
595 Shrewsbury Avenue, Suite 100
Shrewsbury, New Jersey 07702
Telephone: 732-530-9404
Facsimile: 732-530-9808

FAX RECEIVED**AUG 27 2003****GROUP 2600****OFFICIAL**